

BATEMAN



RB25

SPECIFICATIONS

Dimensions

Height	3.8m
Width	2.8m
Length	6.0m
Ground Clearance	0.80m
Wheel Base	3.0m
Turning Radius	4.4m
Weight	5850kg
Fuel Capacity	220 litres

Steering

Positive Link 2/4 wheel steer, fully hydrostatic

Suspension

Hydraulic active front and rear

Wheel Track

Hydraulic adjustable axles with 18 inches variable width

Engine and Transmission

John Deere 170hp, 6 cylinder water cooled Turbo charged diesel

Fully Hydrostatic four wheel drive

Variable from 0 up to 25mph

Primary braking with hydrostatic operated or automatically applied when engine stopped

Cab

Steel construction

Tinted glass

Fully tiltable

Rubber mounted suspension

Carbon filtration

Heater

Fully air conditioned

Radio cassette

Cladded and soundproofed

360° working lights/warning beacon

Fresh water handkeywash

Pneumatically operated step

Air suspension seat with fore and aft movement

Raise, lower and tilt steering column

Airline pickup point

Sprayer

Tank GRP 3000 litres and 200 litre tank wash

Boom Bateman Contour Gull Wing

Width 18,20,24 metre with 12 metre fold

Filling Pump 6 piston diaphragm

Stainless steel hopper, can wash twin ventura selfbooster quick fit

Controls LH5000

Pneumatic diaphragm line valves

Rainbow box

Boom levelling override

Demounting Full set of demount jacks

Wheels

Row crop 12.4/30in

Controls

Joystick forward / reverse and sprayline controls

Hydraulic spools

Options

Twin lines including nozzles

Purge system with triplex nozzles

Spreader skid unit including demount jacks

Bout marker

11.2/30in row crop wheels

Low ground pressure tyres

Bateman Sow Low drill

Air assisted sleeve boom

Twin pump including air plumbing



BATEMAN ENGINEERING LIMITED

BYCOTT, CHUMLEIGH, DEVON, EX18 7DS

Telephone - 01769 580439

Fax - 01769 581023

eMail - mail@bateman-eng.co.uk

We reserve the right to alter specifications without prior notice.

Our policy is one of continuous development.